

SOLAR LAWN LIGHT | WEBSITE FINAL EDITION

A richer decorative range for lawns, pathways, villas and landscape edges.

Low-height solar lawn lights with round, square, bollard, warm-light and stainless-style options for ambience, guidance and retail product programs.



0.5-10W

PRODUCT RANGE

60-1,000 lm

OUTPUT RANGE

12 selections

VISIBLE LINEUP

More than one model - a complete buyer-ready range.

Low-height solar lawn lights with round, square, bollard, warm-light and stainless-style options for ambience, guidance and retail product programs.



01

Source-ready product families

Multiple housings, panel sizes and packaging directions help buyers build a complete market range.

02

OEM/ODM execution

Logo, housing color, color box, manual, label and control profile can be aligned by project.

03

Outdoor quality focus

IP protection, aging inspection, lighting check and packaging review support export programs.

04

Configuration support

Model selection can be matched to application, sunlight hours, working mode and target retail price.

0.5-10W

POWER RANGE

60-1,000 lm

LUMEN RANGE

OEM / ODM

PROJECT SUPPORT

Solar Lawn Light engineering matrix

A compact public specification ladder for first-round selection. Final solar panel, battery reserve, sensor logic and packaging can be tuned by market and project target.

Parameter	0.5W	1W	2W	3W	5W	10W
System flux	60 lm	100 lm	200 lm	300 lm	500 lm	1,000 lm
Solar panel	0.5W	0.8W	1.2W	2W	3W	6W
Battery	3.2V 1Ah	3.2V 1.5Ah	3.2V 2Ah	3.2V 3Ah	3.2V 4Ah	3.2V 8Ah
Height	0.25-0.4 m	0.35-0.5 m	0.45-0.7 m	0.5-0.8 m	0.6-1.0 m	0.8-1.2 m
Application	Marker	Lawn	Pathway	Garden	Villa	Public landscape

CONFIGURATION LOGIC

Use the table as a quoting baseline; Reluxlight can adapt battery size, solar panel, CCT, sensor mode and carton system by order program.

COMMON SPECIFICATIONS

01

IP65 outdoor protection

02

Warm / neutral / RGB option

03

Auto dusk-to-dawn

04

Ground spike or flange base

05

Retail set packaging optional

06

Anti-corrosion finish options

01

Market

retail, project or distributor channel

02

Runtime

working hours and backup-night target

03

Housing

style, finish, mounting and optic

04

Pack



logo, manual, carton and label

PUBLIC DATASHEET NOTE

Public values are prepared for website and quotation discussion. Final configuration is confirmed by project location, order quantity and selected product body.

A complete visual range for market selection.

Twelve visible directions help buyers build a fuller product catalog by style, application and wattage level instead of comparing one isolated model.

 RLL-M01 Mini bollard 0.5-1W Lawn edge	 RLL-R02 Round pole light 1-2W Pathway	 RLL-S03 Square pole light 2-3W Modern garden	 RLL-B04 Bollard diffuser 3-5W Hotel / park
 RLL-P05 Pathway light 3-5W Villa garden	 RLL-W06 Warm ambience light 3-5W Hospitality	 RLL-C07 Classic cone 2-5W Retail range	 RLL-T08 Short cup light 1-3W Landscape set
 RLL-A09 Stainless style 3-8W Premium garden	 RLL-G10 Ground spike set 0.5-2W DIY garden	 RLL-R11 RGB ambience option 1-3W Retail display	 RLL-O12 OEM retail pack 2-5W Chain stores

RELUXLIGHT RANGE ARCHITECTURE

One public series can be packaged into different sales layers: entry retail SKUs, mid-range distributor models, and project-ready configurations for tenders or local installers.

12

visual selections

4

sales layers

OEM

brand support

Turn the series into a project-ready quote.

Reluxlight can help buyers select the right visual style, wattage, battery reserve, working mode and packaging direction for their target market.

01

Lawns

Useful application for this series.

02

Pathways

Useful application for this series.

03

Villa gardens

Useful application for this series.

04

Hotels

Useful application for this series.

05

Parks

Useful application for this series.

06

Landscape edges

Useful application for this series.

07

Retail chains

Useful application for this series.

08

Decoration projects

Useful application for this series.

RELUXLIGHT QUOTATION SUPPORT

- Model ladder by market price level
- Solar panel and battery sizing by working hours
- Logo, manual, color box and carton design
- Sample confirmation before mass production
- Export packaging and document coordination

BEST INQUIRY BRIEF

Send application, installation country, target working hours, backup-night requirement, quantity, logo/packaging needs and any preferred reference model.

info@reluxlight.com

+86 186 1687 2899

Request configuration